M-Cor Inc.

3405 Byron Rd, Helena, MT | 406.227.0477 | customerservice@m-cor.com

Mechanical Properties Data Sheet

Product Information

Product: Teflon Encapsulated O-Ring

Core: FKM (Viton 70 Durometer)

Encapsulation: FEP (Fluorinated Ethylene Propylene)

Size: AS-214

Cross Section: 0.139 in (3.53 mm)

Inside Diameter: 0.984 in (25.0 mm)

Mechanical Properties - Core (FKM 70 Durometer)

Durometer Hardness (Shore A): 70 +- 5 (ASTM D2240)

Tensile Strength: >= 10 MPa (1450 psi) (ASTM D412)

Elongation at Break: >= 200% (ASTM D412)

Compression Set, 22h @ 175 degrees C: <= 25% (ASTM D395 Method B)

Operating Temp Range: -20 degrees C to +205 degrees C

Specific Gravity: ~1.85 (ASTM D297)

Mechanical Properties - Jacket (FEP Teflon)

Durometer Hardness (Shore D): 55-60 (ASTM D2240)

Tensile Strength: >= 25 MPa (3600 psi) (ASTM D638)

Elongation at Break: >= 300% (ASTM D638)

Melting Point: ~260 degrees C (ASTM D3418)

Specific Gravity: ~2.15 (ASTM D792)

Water Absorption: < 0.01% (ASTM D570)

Permeability (H2O/Steam): Very low (ASTM E96 mod)

Functional Properties - Combined

Chemical Resistance: Excellent (FEP jacket)

Dynamic Seal Capability: Moderate (not for high-speed reciprocation)

M-Cor Inc.

3405 Byron Rd, Helena, MT | 406.227.0477 | customerservice@m-cor.com

Vacuum Suitability: Excellent (low outgassing FEP jacket)

Pressure Rating: Up to 1500 psi (static); consult for dynamic

Compression Recovery: Moderate (limited by jacket rebound)

FDA Compliance: CFR 21 177.1550 / 177.2600 (FEP/Viton)

USP Class VI: Pass (typical for encapsulated O-rings)

PFAS Content: Yes (FEP and FKM contain PFAS compounds)

Notes

- FEP jacket limits elasticity - design for minimal stretch during installation.

- Compression set and recovery differ from solid FKM O-rings due to jacket restriction.
- Not recommended for dynamic applications with reciprocating motion.
- Alternative PFAS-free core options (EPDM) available upon request.



© M-Cor Inc. All Rights Reserved.

This document and its contents are the intellectual property of M-Cor Inc., 3405 Byron Rd, Helena, MT. Unauthorized reproduction, distribution, disclosure, or use of any part of this material without the express written permission of M-Cor Inc. is strictly prohibited and may result in legal action. All trademarks, trade names, product names, and logos are the property of M-Cor Inc. or their respective owners. This material may contain proprietary information protected under U.S. and international intellectual property laws.

Violators will be prosecuted to the fullest extent permitted by law.